



# Carefree®

## Floor Finish/Sealer



---

**A multi-surface, multi-maintenance floor finish/sealer that simplifies your floor care program.**

### Versatile

- ▶ Works on nearly all types of floors and responds beautifully to conventional, high-speed or UHS equipment and maintenance procedures
- ▶ Responds to 175 through 2000 rpm equipment

### Long-Lasting Performance

- ▶ A sealer and finish easy on, easy off
- ▶ Exceptional clarity, high gloss and excellent durability

---

### Designed For

- ▶ Education
- ▶ Retail
- ▶ BSC
- ▶ Government



# Use Overview

**Carefree® Floor Sealer/Finish** is a versatile product that works on nearly all types of floors and responds beautifully to conventional, high-speed or UHS equipment and maintenance procedures.

## Applying Floor Finish

- ▶ Strip floor using Diversey stripper according to label instructions.
- ▶ Apply 2–4 coats of finish using a clean mop or the Diversey ProSpeed™<sup>M/MC</sup> or TrailBlazer™<sup>M/MC</sup> Floor Finish Applicator Systems.
- ▶ Apply additional coats if a higher gloss is desired.
- ▶ Allow 30 minutes drying time between coats.

## Maintenance

- ▶ Dust mop or sweep, clean floor with Diversey cleaner following label directions.
- ▶ To enhance gloss, spray buff using recommended Diversey spray maintainer or with red pad and 175–1500 rpm equipment.
- ▶ Dry buff using a white pad and 1000–1500 rpm equipment.
- ▶ UHS burnish with a medium to aggressive pad and 2000+ rpm equipment.

## Product Specifications

Description	
<b>Color/Form</b>	Opaque off-white liquid
<b>Flash Point</b>	> 200° F (> 93.4° C)
<b>pH</b>	8.8
<b>Scent</b>	Ammonia
<b>Shelf Life</b>	2 years
<b>Slip Resistance</b>	0.5 minimum (ASTM D2047)
<b>Solids %</b>	20
<b>Solubility</b>	Dispersible
<b>Specific Gravity</b>	1.029

## Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.



## Before Recoating

- ▶ Dust mop or sweep, and deep scrub floor using Diversey cleaner according to label directions.
- ▶ Apply 1 or 2 coats using a clean mop.

## For Best Results

- ▶ Do not dilute.
- ▶ Do not use on surfaces colder than 10° C (50° F).
- ▶ To avoid contamination, do not return unused finish to original container.
- ▶ Not intended for use on wood.

**Note:** Floors can be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.

## Available Items

Product Code	Description/Package Size	Dilution
05432	4 x 1 gallon / 3.78 L Containers	Ready-To-Use
5104731	1 x 5 gallon / 18.9 L Envirobox™ <sup>M/MC</sup> (TrailBlazer™ <sup>M/MC</sup> ready)*	Ready-To-Use
5383021	6 x 2.64 U.S. Qt. / 2.5 L ProSpeed™ <sup>M/MC</sup> BIB (Bag-in-Box)	Ready-To-Use

\* For best results, use the provided filter when using TrailBlazer™<sup>M/MC</sup>

## Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at [www.diversey.com](http://www.diversey.com) or by calling 888 352 2249.