

# WP 100

**Shurtape®**  
TRUE TO YOUR WORK™

## ECONOMY GRADE, WATER ACTIVATED REINFORCED PAPER TAPE

### TYPICAL APPLICATIONS

- For sealing lightweight cartons up to 20 lbs with minimal exposure to handling, shipping and load stress

### PRODUCT FEATURES

- Excellent tensile strength
- Conformable
- Directly printable
- Paper backing reinforced with fiberglass and PET filaments
- Aggressive water activated adhesive becomes part of the carton

### CONSTRUCTION

Overall Grade/Function: Economy

Backing: Reinforced kraft paper, 110 fiberglass

Adhesive: Water activated

### STANDARD WIDTH(S)

70 mm    72 mm    76 mm

### STANDARD LENGTH(S)

115 m    138 m    153 m

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**NATURAL**  
(NAT)



**WHITE**  
(WHI)

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Top Sheet (Weight)	20 lbs	9.1 kg
Bottom Sheet (Weight)	23 lbs	10.43 kg
Thickness	5.3 mils	0.13 mm
MD Pattern	1-1-1-1	1-1-1-1
MD Spacing	9/16 in	1.4 cm
MD Tensile Strength	63 lbs/in	110.3 N/10 mm
CD Tensile Strength	23 lbs/in	40.3 N/10 mm
CD Spacing	1 in	2.5 cm
Service Temperature Range	-20 F to 120 F	-29 C to 49 C
Application Temperature Range	33 F to 110 F	0.6 C to 43 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

